


# Direct Burial Duct

Duct is manufactured to be in conformance with  
**NEMA TC 6 & 8** and **ASTM F 512**

 Duct is intended for direct burial or concrete encased applications

 Duct is produced with integral solvent-weld bells standard.

<b>DB-100</b>						
Part Number 20'	Size	Dimensions (inches)		Minimum Wall (inches)	Approximate Weight per 100'	Standard Crate Quantity 20'
		OD (Avg)	ID (Approx)			
1030020	3"	3.500	3.26	0.112	94	1,760
1040020	4"	4.500	4.18	0.145	156	1,140
1050020	5"	5.563	5.17	0.179	238	760
1060020	6"	6.625	6.16	0.213	338	520

<b>DB-120</b>						
Part Number 20'	Size	Dimensions (inches)		Minimum Wall (inches)	Approximate Weight per 100'	Standard Crate Quantity 20'
		OD (Avg)	ID (Approx)			
1210020	1	1.315	1.18	0.060	18	8,000
1215020	1 ½"	1.900	1.77	0.060	28	4,500
1220020	2"	2.375	2.21	0.077	44	2,800
1230020	3"	3.500	3.24	0.118	99	1,760
1240020	4"	4.500	4.17	0.154	166	1,140
1250020	5"	5.563	5.15	0.191	254	760
1260020	6"	6.625	6.13	0.227	360	520

**\* DB-60 Available Upon Request. Please call for quote.**